

ProCash 1500xe

Cash Dispenser for indoor use

An optional 15" liquid crystal display is ideal for tapping further sales potential through the integration, for example, of location-specific advertising and information offerings. The range of functions is rounded off by a receipt printer that has full graphics capability and can print custom logos.

In addition to its basic functions of dispensing cash and displaying information the ProCash 1500xe can be extended to meet a financial institution's specific requirements.

- Load/unload electronic purse
- Print receipts or other documents with a full-graphics printer
- Issue tickets or vouchers from versatile cassettes
- Audio systems (loudspeakers/headset)

Features and highlights

- Frontload or rearload
- Compact size
- Standard PC with Pentium III or Celeron
- LCD (12.1" or 15") with autoscaling function
- Output of bundles of up to 60 notes, retract function
- EMV 2000-certified
- Optical indicators at all input and output modules
- Options: advertising attachment, custom colors, logo lighting, labeling in braille



■ The ProCash 1500xe is the entry-level system in Wincor Nixdorf's ProCash product family. With its compact size, it is the ideal system for locations at which space is limited and the focus is on cash handling. Featuring up to four cassettes, the ProCash 1500xe also guarantees maximum availability in installations outside bank foyers, for example at service stations or supermarkets.

ProCash 1500xe

The new "xe-generation"

Further development of Wincor Nixdorf's ProCash product family has resulted in the "xe-generation", which has been optimized technologically to address international customer requirements and trends while retaining its external appearance and overall functionality. The flexibility of these systems is unrivaled on the market when it comes to ideal configuration and availability.

TECHNICAL DATA

SYSTEM CONTROL

Standard PC

DISPLAY

The various VGA, SVGA and XGA resolutions can be implemented on a single display thanks to the autoscaling function.

- 12.1" TFT LCD
- 15" TFT LCD

OPTIONS

- Touchscreen
- Privacy display filter
- Sunlight-readable screen

KEYBOARD

- 8 stainless steel softkeys
- Numeric keypad including 4 function keys

OPTIONS

- Encrypting PIN pad (EPP)
- Encryption/decryption module (EDM)
- Labeling in braille

ELECTRONIC PURSE

Loading and unloading of electronic purses (transaction module for the German GeldKarte)

CARD HANDLING

- Hybrid card reader (motorized)
- EMV 2000-certified
- Tamperproof card slot
- Card retained if not removed, returned in case of power failure

OPTIONS

- DIP reader
- DIP-hybrid reader
- CIM 86 preparation
- Different card retract boxes

CASH DISPENSING

- 1 to 4 cassettes (sealable as standard)
- Max. filling height per cassette: 310 mm / 12,20 in.
- Single reject/bundle retract, storage in separate compartments

OPTIONS

- Cassette with lock
- Cassette with low cash sensor
- Cassette pre-setting

SECURITY

SAFES

- UL 291 Business Hours
- UL 291 Level 1

OPTIONS

- Intruder alarm system (only with UL 291 Level 1)
- Portrait camera

OPTIONS

PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)

MISCELLANEOUS

- Lighted logo area
- Info panel for card symbols
- Loud speakers and/or headset

OPERATING SYSTEM

- Windows NT
- Windows XP

APPLICATION SOFTWARE

- ProClassic
- IBM 473x/PBM Emulation
- NDC (NCR Direct Connect)
- DDC (Diebold Direct Connect)

POWER SUPPLY

110 - 120 V~/220 - 240 V~, 50 - 60 Hz

ENVIRONMENTAL CONDITIONS

Temperature: +5° C to +40° C

(+41° F to +104° F)

Relative humidity: 5% to 85%

COMPLIANCE WITH STANDARDS



Published by
Wincor Nixdorf International GmbH
Heinz-Nixdorf-Ring 1
D-33106 Paderborn
Germany
Phone +49 (0) 52 51/693-3301
Fax +49 (0) 52 51/693-5918
<http://www.wincor-nixdorf.com>

© **Wincor Nixdorf International GmbH**

ProCash® is a registered trademark of
Wincor Nixdorf International GmbH

All rights, including rights created by patent
grant or registration of a utility model or
design, are reserved.

Delivery subject to availability, subject to
change for technical reasons.

Order No. **R10135-J-Z744-1-7600**
Printed in Germany, October 2002